

---

# NI-9402

# Specifications

---

2024-06-07



# Contents

NI-9402 Specifications ..... 3

# NI-9402 Specifications

## Definitions

**Warranted** specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

**Characteristics** describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Typical** unless otherwise noted.

### Related information:

- [Software Support for CompactRIO, CompactDAQ, Single-Board RIO, R Series, and EtherCAT](#)

## Conditions

Specifications are valid for the range -40 °C to 70 °C unless otherwise noted. All voltages are relative to GND unless otherwise noted.

## Input/Output Characteristics

|                       |                |
|-----------------------|----------------|
| Number of channels    | 4 DIO channels |
| Default power-on line | Input          |

|   |                     |
|---|---------------------|
| direction   |                     |
| Input/output type                                       | LVTTL, single-ended |
| <b>Digital logic levels</b>                             |                     |
| Maximum input voltage                                   | 5.25 V              |
| Input high, $V_{IH}$                                    | 2 V minimum         |
| Input low, $V_{IL}$                                     | 0.8 V maximum       |
| <b>Output high, <math>V_{OH}</math> (3.4 V maximum)</b> |                     |
| Sourcing 100 $\mu$ A                                    | 3.0 V minimum       |
| Sourcing 2 mA   | 2.8 V minimum       |
| <b>Output low, <math>V_{OL}</math></b>                  |                     |
| Sinking 100 $\mu$ A                                     | 0.1 V maximum       |
| Sinking 2 mA  | 0.3 V maximum       |
| <b>Maximum I/O switching frequency</b>                  |                     |
| 4 channels  | 16 MHz              |
| 2 channels  | 20 MHz              |

|  |  |
|--|--|
| I/O propagation delay <sup>1, 2</sup> [2]        | 55 ns maximum, 18 ns typical   |
| I/O pulse width distortion <sup>[2]</sup>        | 25 ns maximum  |
| Input low current, $I_{IL}$ ( $V_{IN} = 0$ V)    | -55 $\mu$ A maximum  |
| Input high current, $I_{IH}$ ( $V_{IN} = 4.5$ V) | 150 $\mu$ A maximum  |
| <b>Input impedance</b>                           |  |
| Input capacitance                                | 50 pF maximum  |
| Input resistance                                 | 49 k $\Omega$ minimum  |
| Input rise/fall rate                             | 10 ns/V maximum  |
| Input protection                                 | $\pm 30$ V maximum on one channel at a time  |
| MTBF   | 1,482,777 hours at 25 °C; Bellcore Issue 2, Method 1, Case 3, Limited Part Stress Method |

1. Propagation delay is the maximum amount of time it takes for an input or output signal to propagate between the backplane and the I/O connector, and does not include any additional delay introduced by the cable.
2. Measured at the I/O connector of a load with requirements similar to the NI-9402 and driven through a 2 m coaxial cable.

## Safety Voltages

Connect only voltages that are within the following limits:

|                         |               |
|-------------------------|---------------|
| Channel-to-earth ground | ±30 V maximum |
| <b>Isolation</b>        |               |
| Channel-to-channel      | None          |
| Channel-to-earth ground | None          |

## Environmental Characteristics

|                    |                                 |
|--------------------|---------------------------------|
| <b>Temperature</b> |                                 |
| Operating          | -40 °C to 70 °C                 |
| Storage            | -40 °C to 85 °C                 |
| <b>Humidity</b>    |                                 |
| Operating          | 10% RH to 90% RH, noncondensing |
| Storage            | 5% RH to 95% RH, noncondensing  |
| Ingress protection | IP40                            |
| Pollution Degree   | 2                               |

|                            |  |
|----------------------------|--|
| Maximum altitude           | 2,000 m  |
| <b>Shock and Vibration</b> |  |
| <b>Operating vibration</b> |  |
| Random                     | 5 g RMS, 10 Hz to 500 Hz   |
| Sinusoidal                 | 5 g, 10 Hz to 500 Hz   |
| Operating shock            | 30 g, 11 ms half sine; 50 g, 3 ms half sine; 18 shocks at 6 orientations |

To meet these shock and vibration specifications, you must panel mount the system.

## Power Requirements

|                                       |                |
|---------------------------------------|----------------|
| <b>Power consumption from chassis</b> |                |
| Active mode                           | 550 mW maximum |
| Sleep mode                            | 1 mW maximum   |
| <b>Thermal dissipation (at 70 °C)</b> |                |
| Active mode                           | 550 mW maximum |
| Sleep mode                            | 1 mW maximum   |

## Physical Characteristics

If you need to clean the module, wipe it with a dry towel.

|              |                 |
|--------------|-----------------|
| Cable        | 50 $\Omega$ BNC |
| Cable length | 2 m maximum     |
| Weight       | 199 g (6.9 oz)  |